

## RJ 45 Keystone Shielded Toolless

P/N: TLKJSC6A07-180



### Application

Voice; T1; ISDN

10BASE-T (IEEE 802.3)

16Mbps Token Ring

(IEEE802.5)

100VG-AnyLAN (IEEE802.12)

100Base-T Ethernet(IEEE 802.3u)

155/622 Mbps 1.2/ 2.4 Gbps

ATM

1000Mbps Gigabit Ethernet

550 MHz Broadband video

### PHYSICAL CHARACTERISTICS

STP 180° High density

Toolless, easy termination, no punch down tool needed

Accept 22~24AWG, stranded or solid wire

Diecasting housing design

Comply with FCC part 68 Subpart F and IEC 60603-7

Housing: High-impact, FLAME-RETARDANT

plastic, UL94V-0 rated, spring wire/contact blades

Contact material: Phosphor bronze alloy

Contact plating: 3μ gold plated

Shell:Ninc alloy full shielded

Wiring: T568A/B

## MECHANICAL CHARACTERISTICS

Plug insertion life	1.5 AMPS
Insulation resistance	500 Mega –Ohms min.
Contact Resistance	20 milli-Ohms max.
Dielectric with Standing voltage	1000 V, Rms , 60 HZ, 1 min

## INDUSTRY STANDARD

- UL Listed
- Meets IEEE 802.3 ab Speciation
- High performance, exceeds TIA/EIA-568.2-10 Channel performance.

## ORDER INFORMATION

<b>TLKJSC6A07-180</b>	Toolless RJ45 CAT6A 180 Deg Keystone Jack shielded 568A/B Wiring, White Colour
-----------------------	--