

The compact termination box is designed for use in residential and business applications for the termination of up to four Fibers. The wall box enables the installation of either a single Sirocco Blown Tube cable using up to a 4 fiber blown unit or two 2 fiber Ruggedized cables to be spliced to four SC pigtails (PC or APC), which connect to adapters at the base of the unit.

The unit can be quickly installed within an office, house or communication room environment. SFTH02-XX Wall outlet with 2 positions SC simplex, duplex with shuttered doors Unloaded.



FEATURES & BENEFITS

Compact Design for installation as well as inside the terminal panel	Ability to allow cables to enter from rear or bottom of the unit
Ergonomic design	30mm minimum bend radius
Optical removable rear entry cable management	Flip tray to allow access to pigtails and cable entry
Removable cover for easy access	Unit manufactured from fire UL94-V0 rated material
Tamper proof cover security screws available as an optional	Standard color white

TECHNICAL CHARACTERISTICS

Number of Splice Trays	1
Maximum Fiber Capacity	4
Numbers of Customer feed	4 Patch Cord
Operating Temperature	-20° C to +50°
Materials	FR High Impact Polystyrene
Testing	Optical Tested: 1310nm, 1550nm and 1625nm

APPLICATION

FTTH, FTTO, FTTD Application	LAN, WAN Network & Indoor Application
------------------------------	---------------------------------------

ORDERING INFORMATION

SFTH01-XX	Superiortec Wall Outlet with 2 position SC Simplex, LC Duplex with Shuttered Doors
XX: 00 (Unloaded Box)	ET (1No. SC APC Simplex Adapter)
	DU (1No. LC APC Duplex Adapter + 2No. LC APC Pigtails)
SFTH02-XX	Superiortec Wall Outlet with 2 position SC Simplex, Duplex with Shuttered Doors (Unloaded)
SFTH04-XX	Superiortec Wall Outlet with 4 position SC Simplex, LC Duplex with Shuttered Doors (Unloaded)